

# Light Bulb Removal and Replacement Procedure







**Tools required:**



Before you begin, read and understand all steps of the procedure before beginning so as to familiarize yourself with what is required. Use common sense and always work safe.

1	<p>Turn electrical power off to your spa by turning off its GFCI breaker.</p> <p><b>Note:</b> It is recommended that you lock this GFCI breaker box so that no one can accidentally turn the power back on while you are working.</p>	
2	<p>Behind trim buttons<sup>1</sup> there are eight #2 Phillips screws holding this panel on: 3 on the left trim piece, 3 on the right trim piece, and 2 on the bottom. Remove the trim pieces and then the bottom screws. As you remove the bottom screws, this panel will fall. Lift the panel out of the way and store all parts in a safe place.</p> <p><b>CAUTION:</b> This panel weighs at least 10 pounds and will fall down to the ground as the bottom screws are removed. Keep your feet clear of the bottom of the panel and be prepared for this to happen.</p>	
3	<p>Unplug the black spa pack power cord from its receptacle in the grey box.</p>	
4	<p>The spa light is located behind the rear panel (opposite that of the spa pack panel). Remove the rear panel.</p>	

<sup>1</sup> Some spas do not use trim buttons to cover the screws.

5	<p>Grasp the black bulb holder with your hand and turn it 1/4 turn counter-clockwise. Pull the holder and bulb out of the fixture.</p> <p><b>Note:</b> If the light is an LED fixture, the LED will not come out in this way. Do not remove the black bulb holder. Instead, use the 1/8" slotted screwdriver to remove the white cap housing and remove the LED from the other side.</p>	
6	<p>Pull the bulb out of the socket and replace it with a new bulb (part number <b>B912H</b>).</p> <p><b>Note:</b> If the light is an LED fixture, replace with a new LED (part number <b>510287</b>).</p>	
7	<p>Grasp the black bulb holder with your hand and insert the holder and bulb back into the fixture. Turn the holder 1/4 turn clockwise until it stops.</p> <p><b>Note:</b> If the light is an LED fixture, replace the white cap housing.</p>	
8	<p>Plug in the spa pack.</p>	
9	<p>Turn on the GFCI breaker.</p>	
10	<p>Go to the topside control panel and turn on the light to make sure it works.</p>	
11	<p>Replace the silver insulation and all panels. Place the trim buttons over the screws (if present).</p> <p><b>Tip:</b> It is safest to have two people install these panels: one holding the panel in place while the other puts in the screws.</p>	